



性能:

- 额定电流: 2.0A
- 额定电压: 12V
- 耐电压: 500V
- 接触电阻: 30mΩ
- 绝缘电阻: 500MΩ
- 工作温度: -40℃~+85℃
- 塑件(材质): LCP
- 接触点(材质): 磷铜, 触点镀金3U"

RECOMMENDED PCB LAYOUT  
TOL:(±0.05)



规格	DIM A	DIM B	DIM C
BHC029-3PD720	7.2	5.6	6.5
BHC029-3PD680	6.8	5.2	6.1
BHC029-3PD600	6.0	4.4	5.3
BHC029-3PD540	5.4	3.8	4.7
BHC029-3PD500	5.0	3.4	4.3
BHC029-3PD460	4.6	3.0	3.9

DESIGN	MISS ZENG	SC ALL		未注公差 T00LERANCE		品名: 电池连接器	
DRAWIGN	MISS LI	ANIT		MM	X. ±0.35		X.XX ±0.15
CHECK	Mr. ZENG	SIZE		A4: 210*297	X. X ±0.25		X. XXX ±0.05
APPROVAL		VERSION		01			

型号: BHC029-3PD540



**东莞市航宏电子科技有限公司**  
Dongguan Hanghong Electronics Co., Ltd.