



NOTES:
 1.MECHANICAL:
 MATING FORCE: 5-20N .
 UNMATING FORCE: 8-20N .
 DURABILITY: 10000 CYCLES MIN.
 2.ELECTRICAL:
 CURRENT: 5.0A MAX
 VOLTAGE: 20V MAX
 WITHSTANDING VOLTAGE: 100V AC
 CONTACT RESISTANCE: 40 mΩ MAX INITIAL;
 50 mΩ MAX AFTER 10000 CYCLES
 3.ENVIRONMENTAL
 OPERATING TEMPERATURE RANGE -30°C ~ +80°C

USB TYPE C 接线示意图

A4、A9、B9、B4	V
A5	
B5	
A1、A12、B1、B12	G
A6	D+
A7	D-
(R1=56KΩ R3=56KΩ) 5%	



参观表

产品料号	规格
HH-TYPE162CY30	LCP黑
HH-TYPE162CY31	LCP白

④	GND LATCH	1	STAINLESS STEEL	NICKEL PLATED OVERALL,TAB WITH LEAD FREE TIN ALLOY.	
③	CONTACT	16	COPPER ALLOY	NICKEL UNDERPLATING OVER ALL,GOLD PLATING AT - CONTACT AREA,LEAD FREE TIN ALLOY AT TERMINATION.	
②	SHELL	1	STAINLESS STEEL	CLEAN.	
①	HOUSING	2	THERMOPLASTIC UL 94V-0	MOLDED COLOR:BLACK,white	
4	NO.	DESCRIPTION	QTY.	MATERIAL	TREATMENT

DESIGN	MISS ZENG	SC ALL			未注公差 T00LERANCE	品名: 连接器
DRAWIGN	MISS LI	ANIT	MM			型号: TYPE-C 16P直插/夹板公头
CHECK	Mr. ZENG	SIZE	A4: 210*297			H=12.74MM
APPROVAL		VERSION	01			

东莞市航宏电子科技有限公司
 Dongguan Hanghong Electronics Co., Ltd.