










REV.	ECN. NO.	DESCRIPTION	ENG	DATE
A				

NOTES:

SPECIFICATION:

1. CURRENT RATING: 5.0A MAX
2. VOLTAGE: 100 VAC
3. TEMPERATURE RANGE: -30 °C ~ 85 °C
4. CONTACT RESISTANCE: 40 MILLIONHM MAX
5. INSULATION RESISTANCE: 100 MEGOHMS MIN.
6. INSERTION FORCE : 6N~20N
7. UNMATING FORCE: 8N~20N
8. DURABILITY: 10,000 CYCLES



尼龙料

A1	GND	B12	GND
A4	VBUS	B9	VBUS
A5	CC1	B8	SBU2
A6	DP1	B7	DN2
A7	DN1	B6	DP2
A8	SBU1	B5	CC2
A9	VBUS	B4	VBUS
A12	GND	B1	GND
PIN	SIGNAL NAME	PIN	SIGNAL NAME

NO.	DESCRIPTION	MATERIAL	REMARKS	QTY
6	OVER SHELL	STAINLESS STEEL	NI Plated	1PCS
5	SHIELDING PLATE	STAINLESS STEEL	---	1PCS
4	MD	HIGH TEMPERATURE PLASTIC	PA9T- BLACK	1PCS
3	CONTACT	COPPER ALLOY	Au/Ni Plated	1SET
2	CONTACT	COPPER ALLOY	Au/Ni Plated	1SET
1	HOUSING	HIGH TEMPERATURE PLASTIC	PA9T -BLACK	1PCS

DESIGN	MISS ZENG	SC ALL			未注公差	TOOLERANCE	品名:
DRAWIGN	MISS LI	ANIT	MM		X. ±0.50	X°. ±2°	连接器
CHECK	Mr. ZENG	SIZE	A4: 210*297	X. ±0.30	X°. ±1°	型号:	CUSTOMER DRAWING C F 单排16P 防水型 7.85 母座
APPROVAL		VERSION	01	XX ±0.20	XX° ±0.5°		
				XXX ±0.10			



东莞市航宏电子科技有限公司
Dongguan Hanghong Electronics Co., Ltd.