











专利产品



NOTES:

SPECIFICATION:

1. CURRENT RATING: 5.0A MAX
2. VOLTAGE: 100 VAC
3. TEMPERATURE RANGE: -30 °C ~ 85 °C
4. CONTACT RESISTANCE: 40 MILLIONHM MAX
5. INSULATION RESISTANCE: 100 MEGOHMS MIN.
6. LNSERTION FORCE : 5N~20N
7. UNMATING FORCE: 8N~20N
8. DURABILITY: 10,000 CYCLES



A1	GN1	B12	GN2
A4	VBUS	B5	VBUS
A5	CC	B6	SBUS2
A6	DP1	B7	DM2
A7	DW1	B8	DP2
A8	SBUS1	B5	CC2
A9	VBUS	B4	VBUS
A12	GN2	B1	GN1
PIN	SIGNAL NAME	PIN	SIGNAL NAME

8	DIAN JIAO	WATERPROOF RESIN	BLACK	1PCS
7	UV JIAO	UV JIAO	RED	1PCS
6	EMC	STAINLESS STEEL	NO Plated	1PCS
5	SHELL	STAINLESS STEEL	Ni Plated	1PCS
4	SHIELDING PLATE	STAINLESS STEEL	NO Plated	1PCS
3	CONTACT	COPPER ALLOY	Au1+1U"/Ni Plated	1SET
2	CONTACT	COPPER ALLOY	Au1+1U"/Ni Plated	1SET
1	HOUSING	HIGH TEMPERATURE PLASTIC	BLACK	1PCS
NO.	DESCRIPTION	MATERIAL	REMARKS	QTY

DESIGN	MISS ZENG	SC ALL	
DRAWIGN	MISS LI	ANIT	MM
CHECK	Mr. ZENG	SIZE	A4: 210*297
APPROVAL		VERSION	01

未注公差 TOLERANCE	
X ±0.50	X° ±2°
.X ±0.30	.X° ±1°
.XX ±0.20	.XX° ±0.5°
XXX ±0.10	

品名: 连接器  
 型号: TYPE-C F 16P submerged 2.1 waterproof X7 CONN

东莞市航宏电子科技有限公司  
 Dongguan Hanghong Electronics Co., Ltd.